



HOWARD STEIN HUDSON

114 Turnpike Road, Suite 2C  
Chelmsford, MA 01824  
www.hshassoc.com

PREPARED FOR:

FRH REALTY LLC  
c/o FAIRFIELD RESIDENTIAL  
5 BURLINGTON WOODS, SUITE 203  
BURLINGTON, MA 01803

PROPOSED MULTIFAMILY  
DEVELOPMENT  
SUMMER STREET  
WALPOLE, MA

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



SITE PLAN

LAYOUT AND  
MATERIALS PLAN  
3 OF 5

DATE: JUNE 20, 2023

PROJECT NUMBER: 19097



DESIGNED BY: PB/KE/KF

DRAWN BY: PB/MB/KF/KL


CHECKED BY: KE

C.16

SHEET 16 OF 65



9/20/2023, L:\19097\19097\_04 - Lot 2\CURRENT\19097 - layout and materials.dwg  
Matthew Baker



PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY  
 DEVELOPMENT  
 SUMMER STREET  
 WALPOLE, MA**

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



SITE PLAN

LAYOUT AND MATERIALS PLAN  
 4 OF 5

|                 |               |
|-----------------|---------------|
| DATE:           | JUNE 20, 2023 |
| PROJECT NUMBER: | 19097         |
| DESIGNED BY:    | PB/KE/KF      |
| DRAWN BY:       | PB/MB/KF/KL   |
| CHECKED BY:     | KE            |



9/20/2023 L:\19097\19097.04 - Lot 2\CURRENT\19097 - layout and materials.dwg  
 Matthew Baker



**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY  
 DEVELOPMENT  
 SUMMER STREET  
 WALPOLE, MA**


REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |

**SITE  
 PLAN**

**LANDSCAPING  
 PLAN 4 OF 5**

DATE: JUNE 20, 2023  
 PROJECT NUMBER: 19097  
 DESIGNED BY: PB/KE/KF  
 DRAWN BY: PB/MB/KF/KL  
 CHECKED BY: KE  
 C.32




**LANDSCAPE LEGEND**

- PROPOSED DECIDUOUS TREE
- PROPOSED ORNAMENTAL TREE
- PROPOSED EVERGREEN
- PROPOSED PERENNIAL FLOWER/GRASS

**james k. emmanuel | associates**  
 LANDSCAPE ARCHITECTS

22 Carlton Rd.  
 Marblehead, MA 01945  
 tel. (781) 622-7487

james@jamesemmanuel.com  
 www.jamesemmanuel.com



**STREET TREE PLANTINGS**

**Plant Schedule**




|                                | Botanical Name                  | Common Name       | Size  |
|--------------------------------|---------------------------------|-------------------|-------|
| <b>DECIDUOUS TREE OPTIONS:</b> |                                 |                   |       |
|                                | Acer rubrum 'Red Sunset'        | Red Sunset Maple  | 2"cal |
|                                | Acer saccharum 'Green Mountain' | Sugar Maple       | 2"cal |
| **                             | Carpinus caroliniana            | American Hornbeam | 2"cal |
|                                | Carya ovata                     | Shagbark Hickory  | 2"cal |
| **                             | Ostrya virginiana               | Hophornbeam       | 2"cal |
| **                             | Platanus x acerifolia           | London Planetree  | 2"cal |
| **                             | Quercus coccinea                | Scarlet Oak       | 2"cal |
| **                             | Quercus palustris               | Pin Oak           | 2"cal |
| **                             | Tilia americana                 | Basswood          | 2"cal |
| **                             | Tilia cordata 'Greenspire'      | Greenspire Linden | 2"cal |
| **                             | Zelkova serrata                 | Japanese Zelkova  | 2"cal |

**PLANTING NOTES**

1. THE NUMBER OF EACH INDIVIDUAL PLANT TYPE AND SIZE IS PROVIDED IN THE PLANT LIST FOR CONTRACTORS CONVENIENCE ONLY. IF A DISCREPANCY EXISTS BETWEEN THE NUMBER OF PLANTS ON THE LIST AND THE NUMBER SHOWN ON THE DRAWING, THE GREATER NUMBER SHALL APPLY.
2. ALL PLANT MATERIAL SHALL BE APPROVED BY THE LANDSCAPE ARCHITECT OR THE OWNER'S REPRESENTATIVE PRIOR TO ARRIVAL ON SITE.
3. PLANT MATERIAL SHALL BEAR THE SAME RELATIONSHIP TO FINISHED GRADE AS TO THE ORIGINAL PLANTING GRADE.
4. THE CONTRACTOR SHALL LOCATE AND MARK ALL UTILITIES PRIOR TO PLANTING. ANY CONFLICTS BETWEEN PLANTING AND UTILITIES SHALL BE IMMEDIATELY REPORTED TO THE LANDSCAPE ARCHITECT SO THAT ALTERNATE PLANTING LOCATIONS CAN BE DETERMINED.
5. NO SUBSTITUTION OF PLANT MATERIALS WILL BE ALLOWED WITHOUT THE PRIOR WRITTEN APPROVAL OF THE LANDSCAPE ARCHITECT.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL PLANTS AGAINST DAMAGE FROM ON-GOING CONSTRUCTION. PROTECTION SHALL BEGIN AT THE TIME THE PLANT IS INSTALLED AND CONTINUE UNTIL FORMAL ACCEPTANCE OF ALL PLANTING.
7. ALL DISTURBED AREAS NOT OTHERWISE DEVELOPED SHALL BE LOAMED 6" AND SEEDDED.

**GENERAL LANDSCAPE NOTES:**

1. AREAS NOT OTHERWISE DEVELOPED SHALL RECEIVE MINIMUM 6" COMPACTED DEPTH SCREENED LOAM.
2. EXISTING LOAM TO BE STOCKPILED FOR REUSE.
3. FINISH COVER OVER PLANTING BED SHALL INCLUDE 3" MINIMUM DEPTH PINE MULCH.
4. FINISH SURFACE SHALL BE GRADED FROM A HIGH POINT AT CENTER OF ISLAND OUT TO THE BACK OF CURB. SEE GRADING, DRAINAGE AND PAVING PLAN FOR FINISH GRADES.
5. AT A MINIMUM, TREES AND SHRUBS SHALL BE WATERED BY FLOODING AS FOLLOWS: MONTH 0-3: ONCE PER WEEK MONTH 3-6: TWICE PER MONTH MONTH 6-12: ONCE PER MONTH INCREASE WATERING FREQUENCY TO ACCOUNT FOR DROUGHT CONDITIONS AS REQUIRED.
6. TURF AREAS TO BE WATERED AND MOWED UNTIL ACCEPTED.
7. CONSERVATION SEED MIX AREA TO BE WATERED IF NECESSARY FOR ESTABLISHMENT
8. ALL SIGNAGE LIGHTING SHALL COMPLY WITH WALPOLE ZONING BY-LAWS PER SECTION 7. ALL SIGNAGE LIGHTING SHALL BE LIMITED TO WHITE STEADY, STATIONARY LIGHT OF A REASONABLE INTENSITY THAT IS DIRECTED SOLELY AT THE SIGN AND SHIELDED FROM ADJACENT PARCELS.
9. LANDSCAPE LIGHTING SHALL BE LIMITED TO LIGHTING OF TREES, SHRUBS, OR OTHER PLANT MATERIAL. LIGHTING SHALL BE "LOW-LEVEL LIGHT FIXTURES" (3 FEET OR LOWER) AND ONLY BE DIRECTED IN A DOWNWARD FACING DIRECTION. SEASONAL LIGHTING SHALL NOT BE PERMITTED FOR LONGER THAN A SIX-WEEK PERIOD IN ANY CALENDAR YEAR.



**TOWNHOUSE PLANTINGS**

| SYMBOL                             | FLOWERING TREE OPTIONS:  | SHRUB OPTIONS:    |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
|------------------------------------|--|-------------------|----------------|-------|----------------|---------------|-------|-----------------|----------------|-------|---------------|-----------------|-------|--------------------------|----------------------|-------|---------------------------|-----------------|-------|---------------------|---------------------|-------|--|-----------------------------|-----------------------------|------|-----------------|--------------|------|--------------|-----------|------|---------------------------|-------------------|------|----------------------|-------------|------|-------------------|---------------------|------|---------------------|-----------------|------|-------------------------|-------------------|------|------------------------------------|------------------|------|--------------------|------------|------|---------------------|--------------|------|----------------------|-----------|------|
|                                    | <table border="1"> <tr><td>Cercis canadensis</td><td>Eastern Redbud</td><td>2"cal</td></tr> <tr><td>Cornus florida</td><td>White Dogwood</td><td>2"cal</td></tr> <tr><td>** Cornus kousa</td><td>Korean Dogwood</td><td>2"cal</td></tr> <tr><td>** Cornus mas</td><td>Corneliancherry</td><td>2"cal</td></tr> <tr><td>** Crataegus phaenopyrum</td><td>Washington Hawthorne</td><td>2"cal</td></tr> <tr><td>** Magnolia x soulangiana</td><td>Saucer Magnolia</td><td>8-10'</td></tr> <tr><td>** Sophora japonica</td><td>Japanese Pagodatree</td><td>2"cal</td></tr> </table> | Cercis canadensis | Eastern Redbud | 2"cal | Cornus florida | White Dogwood | 2"cal | ** Cornus kousa | Korean Dogwood | 2"cal | ** Cornus mas | Corneliancherry | 2"cal | ** Crataegus phaenopyrum | Washington Hawthorne | 2"cal | ** Magnolia x soulangiana | Saucer Magnolia | 8-10' | ** Sophora japonica | Japanese Pagodatree | 2"cal | <table border="1"> <tr><td>Cornus alba 'Elegantissima'</td><td>Variegated Red Twig Dogwood</td><td>2-3'</td></tr> <tr><td>Cornus racemosa</td><td>Grey Dogwood</td><td>2-3'</td></tr> <tr><td>** Forsythia</td><td>Forsythia</td><td>2-3'</td></tr> <tr><td>** Ilex glabra 'Shamrock'</td><td>Shamrock Inkberry</td><td>2-3'</td></tr> <tr><td>** Ilex verticillata</td><td>Winterberry</td><td>2-3'</td></tr> <tr><td>** Itea virginica</td><td>Virginia Sweetspire</td><td>2-3'</td></tr> <tr><td>** Kalnia latifolia</td><td>Mountain Laurel</td><td>2-3'</td></tr> <tr><td>** Myrica pennsylvanica</td><td>Northern Bayberry</td><td>2-3'</td></tr> <tr><td>** Physocarpus opulifolius 'Monlo'</td><td>Diabolo Ninebark</td><td>2-3'</td></tr> <tr><td>** Prunus Maratima</td><td>Beach Plum</td><td>2-3'</td></tr> <tr><td>** Syringa vulgaris</td><td>Common Lilac</td><td>2-3'</td></tr> <tr><td>** Viburnum dentatum</td><td>Arrowwood</td><td>2-3'</td></tr> </table> | Cornus alba 'Elegantissima' | Variegated Red Twig Dogwood | 2-3' | Cornus racemosa | Grey Dogwood | 2-3' | ** Forsythia | Forsythia | 2-3' | ** Ilex glabra 'Shamrock' | Shamrock Inkberry | 2-3' | ** Ilex verticillata | Winterberry | 2-3' | ** Itea virginica | Virginia Sweetspire | 2-3' | ** Kalnia latifolia | Mountain Laurel | 2-3' | ** Myrica pennsylvanica | Northern Bayberry | 2-3' | ** Physocarpus opulifolius 'Monlo' | Diabolo Ninebark | 2-3' | ** Prunus Maratima | Beach Plum | 2-3' | ** Syringa vulgaris | Common Lilac | 2-3' | ** Viburnum dentatum | Arrowwood | 2-3' |
| Cercis canadensis                  | Eastern Redbud   | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| Cornus florida                     | White Dogwood  | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Cornus kousa                    | Korean Dogwood   | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Cornus mas                      | Corneliancherry  | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Crataegus phaenopyrum           | Washington Hawthorne   | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Magnolia x soulangiana          | Saucer Magnolia  | 8-10'             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Sophora japonica                | Japanese Pagodatree  | 2"cal             |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| Cornus alba 'Elegantissima'        | Variegated Red Twig Dogwood  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| Cornus racemosa                    | Grey Dogwood   | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Forsythia                       | Forsythia  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Ilex glabra 'Shamrock'          | Shamrock Inkberry  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Ilex verticillata               | Winterberry  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Itea virginica                  | Virginia Sweetspire  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Kalnia latifolia                | Mountain Laurel  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Myrica pennsylvanica            | Northern Bayberry  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Physocarpus opulifolius 'Monlo' | Diabolo Ninebark   | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Prunus Maratima                 | Beach Plum   | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Syringa vulgaris                | Common Lilac   | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |
| ** Viburnum dentatum               | Arrowwood  | 2-3'              |                |       |                |               |       |                 |                |       |               |                 |       |                          |                      |       |                           |                 |       |                     |                     |       |  |                             |                             |      |                 |              |      |              |           |      |                           |                   |      |                      |             |      |                   |                     |      |                     |                 |      |                         |                   |      |                                    |                  |      |                    |            |      |                     |              |      |                      |           |      |


**Conservation Seed Mix**  
 Creeping Red Fescue, (Festuca rubra), Canada Wild Rye, (Elymus canadensis), Annual Ryegrass, (Lolium multiflorum), Perennial Ryegrass, (Lolium perenne), Blue Grama, (Bouteloua gracilis), Little Bluestem, (Schizachyrium scoparium), Indian Grass, (Sorghastrum nutans), Rough Bentgrass, (Agrostis scabra), Upland Bentgrass, (Agrostis perennans)  
 APPLICATION RATE: 35 lbs/acre | 1250 sq ft/lb

**Wildflower Seed Mix**  
 SPECIES:  
 Little Bluestem (Schizachyrium scoparium), Red Fescue (Festuca rubra), Indian Grass (Sorghastrum nutans), Partridge Pea (Chamaecrista fasciculata), Canada Wild Rye (Elymus canadensis), Virginia Wild Rye (Elymus virginicus), Blue Vervain (Verbena hastata), Butterfly Milkweed (Asclepias tuberosa), Narrowleaved Blue Eyed Grass (Sisyrinchium angustifolium), Black Eyed Susan (Rudbeckia hirta), New England Aster (Symphyotrichum novae-angliae), Spiked Gayfeather/ Marsh Blazing Star (Liatris spicata), Starved/Calico Aster (Aster lateriflorus/Symphotrichum lateriflorum), Early Goldenrod (Solidago juncea), Hollow-Stem Joe Pye Weed (Eupatorium fistulosum/Eutrochium fistulosum)  
 APPLICATION RATE: 23 lbs/acre | 1900 sq ft/lb

**ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS**




| MATERIAL LOCATION | DESCRIPTION  | AASHTO MATERIAL CLASSIFICATIONS   | COMPACTION / DENSITY REQUIREMENT   |
|-------------------|--|---|--|
| D                 | <b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'C' LAYER. | N/A   | PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.  |
| C                 | <b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER. | AASHTO M145 <sup>1</sup><br>A-1, A-2.4, A-3<br><br>OR<br>AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10 | BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN). |
| B                 | <b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.  | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | NO COMPACTION REQUIRED.  |
| A                 | <b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.   | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>  |

PLEASE NOTE:  
 1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE."  
 2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.  
 3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN AND LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.  
 4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.



**NOTES:**

- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.



**NOTE:**  
 1. THE AREA OF INFILTRATION SYSTEMS SHALL BE EXCAVATED TO REMOVE TILL DOWN TO NATURAL SOILS AND SHALL BE WITNESSED BY AN AGENT OF THE TOWN PRIOR TO INSTALLING CRUSHED STONE AND THE UNDERGROUND INFILTRATION SYSTEM. LAYOUT, DESIGN, AND ELEVATIONS PRODUCED BY ADS STORMTECH DESIGN TOOL.  
 2. REFER TO GRADING AND DRAINAGE NOTE 20 ON SHEET 2.

**SC-740 STORMTECH CHAMBER SPECIFICATIONS**

- CHAMBERS SHALL BE STORMTECH SC-740.
- CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (+1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (-5-1R) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
  - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
  - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD. THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
  - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

**SYSTEM DETAILS (2204)**  
 PROPOSED LAYOUT INCLUDES 153 STORMTECH SC-740 CHAMBERS AND 34 ENDCAPS INSTALLED WITH 7" BASE STONE AND 12" COVER STONE. AN ISOLATOR ROW IS ALSO PROPOSED.

|  |        |
|--|--------|
| MAX. ALLOWABLE GRADE (TOP OF PAVE/UNPAVED) | 213.58 |
| MIN. ALLOWABLE GRADE (UNPAVED W/ TRAFFIC)  | 207.58 |
| MIN. ALLOWABLE GRADE (UNPAVED NO TRAFFIC)  | 207.08 |
| TOP OF STONE                               | 206.58 |
| TOP OF SC-740 CHAMBER                      | 205.58 |
| WEIR PLATE INVERT                          | 203.59 |
| 18"x18" BOTTOM MANIFOLD INVERT             | 203.22 |
| 18" BOTTOM CONNECTION INVERT               | 203.22 |
| 24" ISOLATOR ROW INVERT                    | 203.09 |
| BOTTOM OF SC-740 CHAMBER                   | 203.08 |
| BOTTOM OF STONE                            | 202.50 |

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- INSPECTION PORTS (IF PRESENT)
    - REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
    - USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - ALL ISOLATOR PLUS ROWS
    - REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
  - APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAR
  - VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

**NOTES**

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.

**IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM**

- STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740DC-780 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
  - STONESHOOTER LOCATED OFF THE CHAMBER BED.
  - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
  - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4-2" (20-50 mm).
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.


**NOTES FOR CONSTRUCTION EQUIPMENT**

- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740DC-780 CONSTRUCTION GUIDE".
- THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
  - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
  - NO RUBBER Tired LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740DC-780 CONSTRUCTION GUIDE".
  - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310SC-740DC-780 CONSTRUCTION GUIDE".
- FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

**SC-740 TECHNICAL SPECIFICATION**



**NOMINAL CHAMBER SPECIFICATIONS**

|                                 |                                 |
|---------------------------------|---------------------------------|
| SIZE (W X H X INSTALLED LENGTH) | 51.0" X 30.0" X 85.4" (1300 mm) |
| CHAMBER STORAGE                 | 45.9 CUBIC FEET (13.0 m³)       |
| MINIMUM INSTALLED STORAGE*      | 74.9 CUBIC FEET (2.12 m³)       |
| WEIGHT                          | 75.0 lbs. (33.6 kg)             |

\*ASSUMES 6" (152 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS


STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

| PART #                      | STUB         | A              | B              | C            |
|-----------------------------|--------------|----------------|----------------|--------------|
| SC740EPE06T / SC740EPE06BPC | 6" (150 mm)  | 10.9" (277 mm) | 18.5" (470 mm) | 0.5" (13 mm) |
| SC740EPE08T / SC740EPE08BPC | 8" (200 mm)  | 12.2" (310 mm) | 16.5" (419 mm) | 0.6" (15 mm) |
| SC740EPE10T / SC740EPE10BPC | 10" (250 mm) | 13.4" (340 mm) | 14.5" (368 mm) | 0.7" (18 mm) |
| SC740EPE12T / SC740EPE12BPC | 12" (300 mm) | 14.7" (373 mm) | 12.5" (318 mm) | 0.8" (20 mm) |
| SC740EPE14T / SC740EPE14BPC | 14" (350 mm) | 16.0" (406 mm) | 10.5" (267 mm) | 0.9" (23 mm) |
| SC740EPE16T / SC740EPE16BPC | 16" (400 mm) | 17.3" (439 mm) | 8.5" (216 mm)  | 1.0" (25 mm) |
| SC740EPE18T / SC740EPE18BPC | 18" (450 mm) | 18.6" (472 mm) | 6.5" (165 mm)  | 1.1" (28 mm) |
| SC740EPE20T / SC740EPE20BPC | 20" (500 mm) | 19.9" (505 mm) | 4.5" (114 mm)  | 1.2" (30 mm) |
| SC740EPE22T / SC740EPE22BPC | 22" (550 mm) | 21.2" (538 mm) | 2.5" (64 mm)   | 1.3" (33 mm) |
| SC740EPE24B*                | 24" (600 mm) | 18.5" (470 mm) | 0.5" (13 mm)   | 0.1" (3 mm)  |

ALL STUBS, EXCEPT FOR THE SC740EPE24B ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\* FOR THE SC740EPE24B THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL



**SC-740 6" (150 mm) INSPECTION PORT DETAIL**

**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

PROPOSED MULTIFAMILY DEVELOPMENT  
 SUMMER STREET  
 WALPOLE, MA

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



SITE PLAN


STORMTECH INFILTRATION SYSTEM #1  
 (DETAIL SHEET 20 OF 27)

DATE: JUNE 20, 2023  
 PROJECT NUMBER: 19097  
 DESIGNED BY: PB/KE/KF  
 DRAWN BY: PB/MB/KF/KL  
 CHECKED BY: KE

**ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS**


| MATERIAL LOCATION | DESCRIPTION  | AASHTO MATERIAL CLASSIFICATIONS  | COMPACTION / DENSITY REQUIREMENT   |
|-------------------|--|--|--|
| D                 | <b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER. | N/A  | PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.  |
| C                 | <b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER. | GRANULAR WELL-GRADED SOIL/AGGREGATE MIXTURES, <35% FINES OR PROCESSED AGGREGATE.<br>OR<br>MOST PAVEMENT SUBBASE MATERIALS CAN BE USED IN LIEU OF THIS LAYER. | BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 90% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN). |
| B                 | <b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.  | CLEAN, CRUSHED, ANGULAR STONE<br>AASHTO M43<br>3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10   | NO COMPACTION REQUIRED.  |
| A                 | <b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.   | CLEAN, CRUSHED, ANGULAR STONE<br>AASHTO M43<br>3, 357, 4, 467, 5, 56, 57   | PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE <sup>2,3</sup>   |

PLEASE NOTE:  
 1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE."  
 2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.  
 3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.  
 4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.



**NOTES:**


- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-10a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.



**NOTE:**  
 1. THE AREA OF INFILTRATION SYSTEMS SHALL BE EXCAVATED TO REMOVE TILL DOWN TO NATURAL SOILS AND SHALL BE WITNESSED BY AN AGENT OF THE TOWN PRIOR TO INSTALLING CRUSHED STONE AND THE UNDERGROUND INFILTRATION SYSTEM.  
 2. LAYOUT, DESIGN, AND ELEVATIONS PRODUCED BY ADS STORMTECH DESIGN TOOL.  
 3. REFER TO GRADING AND DRAINAGE NOTE 20 ON SHEET 2.

**SC-740 STORMTECH CHAMBER SPECIFICATIONS**

- CHAMBERS SHALL BE STORMTECH SC-740.
- CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-10a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
  - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
  - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
  - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.



| CHAMBER | MAX DIAMETER OF INSERTA TEE | HEIGHT FROM BASE OF CHAMBER (X) |
|---------|-----------------------------|---------------------------------|
| SC-310  | 6" (150 mm)                 | 4" (100 mm)                     |
| SC-740  | 10" (250 mm)                | 4" (100 mm)                     |
| DC-780  | 10" (250 mm)                | 4" (100 mm)                     |
| MC-3500 | 12" (300 mm)                | 6" (150 mm)                     |
| MC-4500 | 12" (300 mm)                | 6" (200 mm)                     |

INSERTA TEE FITTINGS AVAILABLE FOR SDR 26, SDR 35, SCH 40 IPS GASKETED & SOLVENT WELD, N-12, HP STORM, C-900 OR DUCTILE IRON

**IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM**

- STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
  - STONESHOOTER LOCATED OFF THE CHAMBER BED.
  - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
  - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELLED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4"-2" (20-50 mm).
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" SYSTEMS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEMS FROM CONSTRUCTION SITE RUNOFF.


**NOTES FOR CONSTRUCTION EQUIPMENT**

- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
  - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
  - NO RUBBER TRED LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
  - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- FULL 36" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

**SC-740 TECHNICAL SPECIFICATION**



**NOMINAL CHAMBER SPECIFICATIONS**

| SIZE (W X H X INSTALLED LENGTH) | 51.0" X 30.0" X 85.4" (1.30 m <sup>3</sup> ) | (1295 mm X 762 mm X 2169 mm)           |
|---------------------------------|--|--|
| CHAMBER STORAGE                 | 74.9 CUBIC FEET (2.12 m <sup>3</sup> )       | 74.9 CUBIC FEET (2.12 m <sup>3</sup> ) |
| MINIMUM INSTALLED STORAGE*      | 75.0 lbs. (33.6 kg)                          | 75.0 lbs. (33.6 kg)                    |

\*ASSUMES 6" (150 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS


STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

| PART #                    | STUB         | A              | B              | C            |
|---------------------------|--------------|----------------|----------------|--------------|
| SC740EP00T / SC740EP00TPC | 6" (150 mm)  | 10.9" (277 mm) | 18.5" (470 mm) | ---          |
| SC740EP00B / SC740EP00BPC | ---          | ---            | ---            | 0.5" (13 mm) |
| SC740EP08T / SC740EP08TPC | 8" (200 mm)  | 12.2" (310 mm) | 16.5" (419 mm) | ---          |
| SC740EP08B / SC740EP08BPC | ---          | ---            | ---            | 0.0" (15 mm) |
| SC740EP10T / SC740EP10TPC | 10" (250 mm) | 13.4" (340 mm) | 14.5" (368 mm) | ---          |
| SC740EP10B / SC740EP10BPC | ---          | ---            | ---            | 0.7" (18 mm) |
| SC740EP12T / SC740EP12TPC | 12" (300 mm) | 14.7" (373 mm) | 12.5" (318 mm) | ---          |
| SC740EP12B / SC740EP12BPC | ---          | ---            | ---            | 1.2" (30 mm) |
| SC740EP15T / SC740EP15TPC | 15" (375 mm) | 18.4" (467 mm) | 9.0" (229 mm)  | ---          |
| SC740EP15B / SC740EP15BPC | ---          | ---            | ---            | 1.3" (33 mm) |
| SC740EP18T / SC740EP18TPC | 18" (450 mm) | 19.7" (500 mm) | 5.0" (127 mm)  | ---          |
| SC740EP18B / SC740EP18BPC | ---          | ---            | ---            | 1.6" (41 mm) |
| SC740EP24B*               | 24" (600 mm) | 18.5" (470 mm) | ---            | 0.1" (3 mm)  |

ALL STUBS, EXCEPT FOR THE SC740EP24B ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\* FOR THE SC740EP24B THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL



**SC-740 6" (150 mm) INSPECTION PORT DETAIL**

**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY DEVELOPMENT**  
 SUMMER STREET  
 WALPOLE, MA

**REVISIONS:**

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



**SITE PLAN**


**STORMTECH INFILTRATION SYSTEM #2 (DETAIL SHEET 21 OF 27)**

DATE: JUNE 20, 2023  
 PROJECT NUMBER: 19097  
 DESIGNED BY: PB/KE/KF  
 DRAWN BY: PB/MB/KF/KL  
 CHECKED BY: KE

**ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS**

| MATERIAL LOCATION | DESCRIPTION  | AASHTO MATERIAL CLASSIFICATIONS   | COMPACTION / DENSITY REQUIREMENT   |
|-------------------|--|---|--|
| D                 | <b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'D' LAYER. | N/A   | PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.  |
| C                 | <b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER. | AASHTO M145 <sup>1</sup><br>A-1, A-2.4, A-3<br><br>OR<br>AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10 | BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN). |
| B                 | <b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.  | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | NO COMPACTION REQUIRED.  |
| A                 | <b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.   | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>  |

PLEASE NOTE:  
 1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE."  
 2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTIONED IN 6" (150 mm) (MAX) LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.  
 3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.  
 4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.




**NOTES:**  
 1. CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS."  
 2. SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".  
 3. THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.  
 4. PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.  
 5. REQUIREMENTS FOR HANDLING AND INSTALLATION:  
 • TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.  
 • TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".  
 • TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.

**SC-740 STORMTECH CHAMBER SPECIFICATIONS**

- CHAMBERS SHALL BE STORMTECH SC-740.
- CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-YR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:  
 • TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.  
 • TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".  
 • TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, a) THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:  
 • THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.  
 • THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD. THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.  
 • THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

**SC-740 TECHNICAL SPECIFICATION**



**NOMINAL CHAMBER SPECIFICATIONS**

| SIZE (W X H X INSTALLED LENGTH) | CHAMBER STORAGE                        | MINIMUM INSTALLED STORAGE*             | WEIGHT              |
|---------------------------------|--|--|---------------------|
| 51.0" X 30.0" X 85.4"           | 45.9 CUBIC FEET (1.30 m <sup>3</sup> ) | 74.9 CUBIC FEET (2.12 m <sup>3</sup> ) | 75.0 lbs. (33.6 kg) |
| 1295 mm X 762 mm X 2169 mm      |  |  |                     |

\*ASSUMES 6" (152 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS

**IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM**

- STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:  
 • STONES/ROCKER LOCATED OFF THE CHAMBER BED.  
 • BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.  
 • BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4" (20-50 mm).
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "FLEXSTORM CATCH IT" INSERTS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT SYSTEM FROM CONSTRUCTION SITE RUNOFF.

**NOTES FOR CONSTRUCTION EQUIPMENT**

- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:  
 • NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.  
 • NO RUBBER Tired LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".  
 • WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310/SC-740/DC-780 CONSTRUCTION GUIDE".
- FULL 30" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B" STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

| PART #                      | STUB         | A              | B              | C            |
|-----------------------------|--------------|----------------|----------------|--------------|
| SC740EPE06T / SC740EPE06TPC | 6" (150 mm)  | 10.9" (277 mm) | 18.5" (470 mm) | ---          |
| SC740EPE06B / SC740EPE06BPC | 6" (150 mm)  | 12.2" (310 mm) | ---            | 0.5" (13 mm) |
| SC740EPE08T / SC740EPE08TPC | 8" (200 mm)  | 12.2" (310 mm) | 16.5" (419 mm) | ---          |
| SC740EPE08B / SC740EPE08BPC | 8" (200 mm)  | 13.4" (340 mm) | 14.5" (368 mm) | 0.8" (15 mm) |
| SC740EPE10B / SC740EPE10BPC | 10" (250 mm) | 13.4" (340 mm) | 14.5" (368 mm) | 0.7" (18 mm) |
| SC740EPE12T / SC740EPE12TPC | 12" (300 mm) | 14.7" (373 mm) | 12.5" (318 mm) | ---          |
| SC740EPE12B / SC740EPE12BPC | 12" (300 mm) | 18.4" (467 mm) | 9.0" (229 mm)  | 1.2" (30 mm) |
| SC740EPE15T / SC740EPE15TPC | 15" (375 mm) | 18.4" (467 mm) | 5.0" (127 mm)  | 1.3" (33 mm) |
| SC740EPE15B / SC740EPE15BPC | 15" (375 mm) | 18.5" (470 mm) | ---            | 1.6" (41 mm) |
| SC740EPE18T / SC740EPE18TPC | 18" (450 mm) | 18.5" (470 mm) | ---            | 0.1" (3 mm)  |
| SC740EPE18B / SC740EPE18BPC | 18" (450 mm) | 18.5" (470 mm) | ---            | ---          |
| SC740EPE24B*                | 24" (600 mm) | ---            | ---            | ---          |

ALL STUBS, EXCEPT FOR THE SC740EPE24B ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\*FOR THE SC740EPE24B THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.



NOTE: ALL DIMENSIONS ARE NOMINAL.

**SYSTEM DETAILS (P213)**

PROPOSED LAYOUT INCLUDES 136 STORMTECH SC-740 CHAMBERS AND 26 END CAPS INSTALLED WITH 6" BASE STONE AND 6" COVER STONE. AN ISOLATOR ROW IS ALSO PROPOSED.

|   |        |  |
|---|--------|--|
| MAX. ALLOWABLE GRADE (TOP OF UNPAVED)     | 211.95 | ESTIMATED SEASONAL HIGH GROUNDWATER ELEVATION: 200.15± |
| MIN. ALLOWABLE GRADE (UNPAVED W/ TRAFFIC) | 205.95 | GROUNDWATER ELEVATION: 196.48± (44")                   |
| MIN. ALLOWABLE GRADE (UNPAVED NO TRAFFIC) | 205.45 | ESTIMATED SEASONAL HIGH GROUNDWATER ELEVATION: 200.13± |
| TOP OF STONE                              | 204.45 | GROUNDWATER ELEVATION: 197.13± (36")                   |
| TOP OF SC-740 CHAMBER                     | 203.95 | PROPOSED BOTTOM OF SYSTEM: 200.95                      |
| WEIR PLATE INVERT                         | 201.96 | EXISTING GRADE AT PROPOSED SYSTEM: 201.74±             |
| 12"x12" BOTTOM MANIFOLD INVERT            | 201.55 | ESTIMATED GROUNDWATER ELEVATION: 198.74± (36")         |
| 12" BOTTOM CONNECTION INVERT              | 201.55 |  |
| 24" ISOLATOR ROW INVERT                   | 201.46 |  |
| BOTTOM OF SC-740 CHAMBER                  | 201.45 |  |
| BOTTOM OF STONE                           | 200.95 |  |

- NOTE:**
- THE AREA OF INFILTRATION SYSTEMS SHALL BE EXCAVATED TO REMOVE TILL DOWN TO NATURAL SOILS AND SHALL BE WITNESSED BY AN AGENT OF THE TOWN PRIOR TO INSTALLING CRUSHED STONE AND THE UNDERGROUND INFILTRATION SYSTEM.
  - ESTIMATED SEASONAL HIGH GROUNDWATER ASSUMED USING TP-39 REFER TO DETAIL CALCULATION PROVIDED ABOVE.
  - LAYOUT, DESIGN, AND ELEVATIONS PRODUCED BY ADS STORMTECH DESIGN TOOL.
  - REFER TO GRADING AND DRAINAGE NOTE 20 ON SHEET 2.




**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT
- INSPECTION PORTS (IF PRESENT)
  - REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
  - REMOVE AND CLEAN FLEXSTORM FILTER IF INSTALLED
  - USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
  - LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
  - IF SEDIMENT IS AT OR ABOVE, 3" (80 mm) PROCEED TO STEP 2; IF NOT, PROCEED TO STEP 3.
- B. ALL ISOLATOR PLUS ROWS
- REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
  - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
    - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
    - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - IF SEDIMENT IS AT OR ABOVE, 3" (80 mm) PROCEED TO STEP 2; IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JETVAC PROCESS
- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45" (1.1 m) OR MORE IS PREFERRED
  - APPLY MULTIPLE PASSES OF JETVAC UNTIL BACKFLUSH WATER IS CLEAN
  - VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.

**NOTES**

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.



**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY DEVELOPMENT**  
**SUMMER STREET**  
**WALPOLE, MA**

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



SITE PLAN

**STORMTECH INFILTRATION SYSTEM #3 (DETAIL SHEET 22 OF 27)**


|                 |               |
|-----------------|---------------|
| DATE:           | JUNE 20, 2023 |
| PROJECT NUMBER: | 19097         |
| DESIGNED BY:    | PB/KE/KF      |
| DRAWN BY:       | PB/MB/KF/KL   |
| CHECKED BY:     | KE            |

C.60

**ACCEPTABLE FILL MATERIALS: STORMTECH SC-740 CHAMBER SYSTEMS**



| MATERIAL LOCATION | DESCRIPTION  | AASHTO MATERIAL CLASSIFICATIONS   | COMPACTION / DENSITY REQUIREMENT   |
|-------------------|--|---|--|
| D                 | <b>FINAL FILL:</b> FILL MATERIAL FOR LAYER 'D' STARTS FROM THE TOP OF THE 'C' LAYER TO THE BOTTOM OF FLEXIBLE PAVEMENT OR UNPAVED FINISHED GRADE ABOVE. NOTE THAT PAVEMENT SUBBASE MAY BE PART OF THE 'C' LAYER. | N/A   | PREPARE PER SITE DESIGN ENGINEER'S PLANS. PAVED INSTALLATIONS MAY HAVE STRINGENT MATERIAL AND PREPARATION REQUIREMENTS.  |
| C                 | <b>INITIAL FILL:</b> FILL MATERIAL FOR LAYER 'C' STARTS FROM THE TOP OF THE EMBEDMENT STONE ('B' LAYER) TO 18" (450 mm) ABOVE THE TOP OF THE CHAMBER. NOTE THAT PAVEMENT SUBBASE MAY BE A PART OF THE 'C' LAYER. | AASHTO M145 <sup>1</sup><br>A-1, A-2.4, A-3<br><br>OR<br>AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57, 6, 67, 68, 7, 78, 8, 89, 9, 10 | BEGIN COMPACTIONS AFTER 12" (300 mm) OF MATERIAL OVER THE CHAMBERS IS REACHED. COMPACT ADDITIONAL LAYERS IN 6" (150 mm) MAX LIFTS TO A MIN. 95% PROCTOR DENSITY FOR WELL GRADED MATERIAL AND 95% RELATIVE DENSITY FOR PROCESSED AGGREGATE MATERIALS. ROLLER GROSS VEHICLE WEIGHT NOT TO EXCEED 12,000 lbs (53 kN). DYNAMIC FORCE NOT TO EXCEED 20,000 lbs (89 kN). |
| B                 | <b>EMBEDMENT STONE:</b> FILL SURROUNDING THE CHAMBERS FROM THE FOUNDATION STONE ('A' LAYER) TO THE 'C' LAYER ABOVE.  | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | NO COMPACTION REQUIRED.  |
| A                 | <b>FOUNDATION STONE:</b> FILL BELOW CHAMBERS FROM THE SUBGRADE UP TO THE FOOT (BOTTOM) OF THE CHAMBER.   | AASHTO M43 <sup>2</sup><br>3, 357, 4, 467, 5, 56, 57  | PLATE COMPACT OR ROLL TO ACHIEVE A FLAT SURFACE. <sup>2,3</sup>  |

PLEASE NOTE:  
 1. THE LISTED AASHTO DESIGNATIONS ARE FOR GRADATIONS ONLY. THE STONE MUST ALSO BE CLEAN, CRUSHED, ANGULAR. FOR EXAMPLE, A SPECIFICATION FOR #4 STONE WOULD STATE: "CLEAN, CRUSHED, ANGULAR NO. 4 (AASHTO M43) STONE."  
 2. STORMTECH COMPACTION REQUIREMENTS ARE MET FOR 'A' LOCATION MATERIALS WHEN PLACED AND COMPACTED IN 6" (150 mm) MAX LIFTS USING TWO FULL COVERAGES WITH A VIBRATORY COMPACTOR.  
 3. WHERE INFILTRATION SURFACES MAY BE COMPROMISED BY COMPACTION, FOR STANDARD DESIGN LOAD CONDITIONS, A FLAT SURFACE MAY BE ACHIEVED BY RAKING OR DRAGGING WITHOUT COMPACTION EQUIPMENT. FOR SPECIAL LOAD DESIGNS, CONTACT STORMTECH FOR COMPACTION REQUIREMENTS.  
 4. ONCE LAYER 'C' IS PLACED, ANY SOIL/MATERIAL CAN BE PLACED IN LAYER 'D' UP TO THE FINISHED GRADE. MOST PAVEMENT SUBBASE SOILS CAN BE USED TO REPLACE THE MATERIAL REQUIREMENTS OF LAYER 'C' OR 'D' AT THE SITE DESIGN ENGINEER'S DISCRETION.



**NOTES:**

- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- SC-740 CHAMBERS SHALL BE DESIGNED IN ACCORDANCE WITH ASTM F2787 "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- THE SITE DESIGN ENGINEER IS RESPONSIBLE FOR ASSESSING THE BEARING RESISTANCE (ALLOWABLE BEARING CAPACITY) OF THE SUBGRADE SOILS AND THE DEPTH OF FOUNDATION STONE WITH CONSIDERATION FOR THE RANGE OF EXPECTED SOIL MOISTURE CONDITIONS.
- PERIMETER STONE MUST BE EXTENDED HORIZONTALLY TO THE EXCAVATION WALL FOR BOTH VERTICAL AND SLOPED EXCAVATION WALLS.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. (AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.



**SC-740 STORMTECH CHAMBER SPECIFICATIONS**

- CHAMBERS SHALL BE STORMTECH SC-740.
- CHAMBERS SHALL BE ARCH-SHAPED AND SHALL BE MANUFACTURED FROM VIRGIN, IMPACT-MODIFIED POLYPROPYLENE COPOLYMERS.
- CHAMBERS SHALL MEET THE REQUIREMENTS OF ASTM F2418-16a, "STANDARD SPECIFICATION FOR POLYPROPYLENE (PP) CORRUGATED WALL STORMWATER COLLECTION CHAMBERS".
- CHAMBER ROWS SHALL PROVIDE CONTINUOUS, UNOBSTRUCTED INTERNAL SPACE WITH NO INTERNAL SUPPORTS THAT WOULD IMPEDE FLOW OR LIMIT ACCESS FOR INSPECTION.
- THE STRUCTURAL DESIGN OF THE CHAMBERS, THE STRUCTURAL BACKFILL, AND THE INSTALLATION REQUIREMENTS SHALL ENSURE THAT THE LOAD FACTORS SPECIFIED IN THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS, SECTION 12.12, ARE MET FOR: 1) LONG-DURATION DEAD LOADS AND 2) SHORT-DURATION LIVE LOADS, BASED ON THE AASHTO DESIGN TRUCK WITH CONSIDERATION FOR IMPACT AND MULTIPLE VEHICLE PRESENCES.
- CHAMBERS SHALL BE DESIGNED, TESTED AND ALLOWABLE LOAD CONFIGURATIONS DETERMINED IN ACCORDANCE WITH ASTM F2787, "STANDARD PRACTICE FOR STRUCTURAL DESIGN OF THERMOPLASTIC CORRUGATED WALL STORMWATER COLLECTION CHAMBERS". LOAD CONFIGURATIONS SHALL INCLUDE: 1) INSTANTANEOUS (<1 MIN) AASHTO DESIGN TRUCK LIVE LOAD ON MINIMUM COVER 2) MAXIMUM PERMANENT (75-TR) COVER LOAD AND 3) ALLOWABLE COVER WITH PARKED (1-WEEK) AASHTO DESIGN TRUCK.
- REQUIREMENTS FOR HANDLING AND INSTALLATION:
  - TO MAINTAIN THE WIDTH OF CHAMBERS DURING SHIPPING AND HANDLING, CHAMBERS SHALL HAVE INTEGRAL, INTERLOCKING STACKING LUGS.
  - TO ENSURE A SECURE JOINT DURING INSTALLATION AND BACKFILL, THE HEIGHT OF THE CHAMBER JOINT SHALL NOT BE LESS THAN 2".
  - TO ENSURE THE INTEGRITY OF THE ARCH SHAPE DURING INSTALLATION, THE ARCH STIFFNESS CONSTANT AS DEFINED IN SECTION 6.2.8 OF ASTM F2418 SHALL BE GREATER THAN OR EQUAL TO 550 LBS/IN. (AND b) TO RESIST CHAMBER DEFORMATION DURING INSTALLATION AT ELEVATED TEMPERATURES (ABOVE 73° F / 23° C), CHAMBERS SHALL BE PRODUCED FROM REFLECTIVE GOLD OR YELLOW COLORS.
- ONLY CHAMBERS THAT ARE APPROVED BY THE SITE DESIGN ENGINEER WILL BE ALLOWED. UPON REQUEST BY THE SITE DESIGN ENGINEER OR OWNER, THE CHAMBER MANUFACTURER SHALL SUBMIT A STRUCTURAL EVALUATION FOR APPROVAL BEFORE DELIVERING CHAMBERS TO THE PROJECT SITE AS FOLLOWS:
  - THE STRUCTURAL EVALUATION SHALL BE SEALED BY A REGISTERED PROFESSIONAL ENGINEER.
  - THE STRUCTURAL EVALUATION SHALL DEMONSTRATE THAT THE SAFETY FACTORS ARE GREATER THAN OR EQUAL TO 1.95 FOR DEAD LOAD AND 1.75 FOR LIVE LOAD, THE MINIMUM REQUIRED BY ASTM F2787 AND BY SECTIONS 3 AND 12.12 OF THE AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS FOR THERMOPLASTIC PIPE.
  - THE TEST DERIVED CREEP MODULUS AS SPECIFIED IN ASTM F2418 SHALL BE USED FOR PERMANENT DEAD LOAD DESIGN EXCEPT THAT IT SHALL BE THE 75-YEAR MODULUS USED FOR DESIGN.
- CHAMBERS AND END CAPS SHALL BE PRODUCED AT AN ISO 9001 CERTIFIED MANUFACTURING FACILITY.

**SYSTEM DETAILS (P214)**  
 PROPOSED LAYOUT INCLUDES 120 STORMTECH SC-740 CHAMBERS AND 24 END CAPS INSTALLED WITH 6" BASE STONE AND 6" COVER STONE. AN ISOLATOR ROW IS ALSO PROPOSED.

|  |        |
|--|--------|
| MAX. ALLOWABLE GRADE (TOP OF PAVE/UNPAVED) | 211.50 |
| MIN. ALLOWABLE GRADE (UNPAVED W/ TRAFFIC)  | 205.00 |
| TOP OF SC-740 CHAMBER                      | 203.50 |
| WEIR PLATE INVERT                          | 201.51 |
| 12"x12" BOTTOM MANIFOLD INVERT             | 201.10 |
| 24" ISOLATOR ROW INVERT                    | 201.01 |
| BOTTOM OF SC-740 CHAMBER                   | 201.00 |
| BOTTOM OF STONE                            | 200.50 |

**ESTIMATED SEASONAL HIGH GROUNDWATER ELEVATION:** 200.71±

**EXISTING GRADE AT PROPOSED SYSTEM:** 202.20±

**ESTIMATED GROUNDWATER ELEVATION:** 198.45± (48")

**INSPECTION & MAINTENANCE**

- STEP 1) INSPECT ISOLATOR ROW PLUS FOR SEDIMENT**
- INSPECTION PORTS (IF PRESENT)
    - REMOVE/OPEN LID ON NYLOPLAST INLINE DRAIN
    - REMOVE AND CLEAN FLEXFORM FILTER IF INSTALLED
    - USING A FLASHLIGHT AND STADIA ROD, MEASURE DEPTH OF SEDIMENT AND RECORD ON MAINTENANCE LOG
    - LOWER A CAMERA INTO ISOLATOR ROW PLUS FOR VISUAL INSPECTION OF SEDIMENT LEVELS (OPTIONAL)
    - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
  - ALL ISOLATOR PLUS ROWS
    - REMOVE COVER FROM STRUCTURE AT UPSTREAM END OF ISOLATOR ROW PLUS
    - USING A FLASHLIGHT, INSPECT DOWN THE ISOLATOR ROW PLUS THROUGH OUTLET PIPE
      - MIRRORS ON POLES OR CAMERAS MAY BE USED TO AVOID A CONFINED SPACE ENTRY
      - FOLLOW OSHA REGULATIONS FOR CONFINED SPACE ENTRY IF ENTERING MANHOLE
    - IF SEDIMENT IS AT, OR ABOVE, 3" (80 mm) PROCEED TO STEP 2. IF NOT, PROCEED TO STEP 3.
- STEP 2) CLEAN OUT ISOLATOR ROW PLUS USING THE JET/VAC PROCESS**
- A FIXED CULVERT CLEANING NOZZLE WITH REAR FACING SPREAD OF 45° (1.1 m) OR MORE IS PREFERRED
  - APPLY MULTIPLE PASSES OF JET/VAC UNTIL BACKFLUSH WATER IS CLEAN
  - VACUUM STRUCTURE SUMP AS REQUIRED
- STEP 3) REPLACE ALL COVERS, GRATES, FILTERS, AND LIDS; RECORD OBSERVATIONS AND ACTIONS.**
- STEP 4) INSPECT AND CLEAN BASINS AND MANHOLES UPSTREAM OF THE STORMTECH SYSTEM.**

**NOTES**

- INSPECT EVERY 6 MONTHS DURING THE FIRST YEAR OF OPERATION. ADJUST THE INSPECTION INTERVAL BASED ON PREVIOUS OBSERVATIONS OF SEDIMENT ACCUMULATION AND HIGH WATER ELEVATIONS.
- CONDUCT JETTING AND VACTORING ANNUALLY OR WHEN INSPECTION SHOWS THAT MAINTENANCE IS NECESSARY.

**IMPORTANT - NOTES FOR THE BIDDING AND INSTALLATION OF THE SC-740 SYSTEM**

- STORMTECH SC-740 CHAMBERS SHALL NOT BE INSTALLED UNTIL THE MANUFACTURER'S REPRESENTATIVE HAS COMPLETED A PRE-CONSTRUCTION MEETING WITH THE INSTALLERS.
- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740/DC-780 CONSTRUCTION GUIDE".
- CHAMBERS ARE NOT TO BE BACKFILLED WITH A DOZER OR AN EXCAVATOR SITUATED OVER THE CHAMBERS. STORMTECH RECOMMENDS 3 BACKFILL METHODS:
  - STONESHOOTER LOCATED OFF THE CHAMBER BED.
  - BACKFILL AS ROWS ARE BUILT USING AN EXCAVATOR ON THE FOUNDATION STONE OR SUBGRADE.
  - BACKFILL FROM OUTSIDE THE EXCAVATION USING A LONG BOOM HOE OR EXCAVATOR.
- THE FOUNDATION STONE SHALL BE LEVELED AND COMPACTED PRIOR TO PLACING CHAMBERS.
- JOINTS BETWEEN CHAMBERS SHALL BE PROPERLY SEATED PRIOR TO PLACING STONE.
- MAINTAIN MINIMUM - 6" (150 mm) SPACING BETWEEN THE CHAMBER ROWS.
- EMBEDMENT STONE SURROUNDING CHAMBERS MUST BE A CLEAN, CRUSHED, ANGULAR STONE 3/4" (20-50 mm).
- THE CONTRACTOR MUST REPORT ANY DISCREPANCIES WITH CHAMBER FOUNDATION MATERIALS BEARING CAPACITIES TO THE SITE DESIGN ENGINEER.
- ADS RECOMMENDS THE USE OF "FLEXFORM CATCH IT" SYSTEMS DURING CONSTRUCTION FOR ALL INLETS TO PROTECT THE SUBSURFACE STORMWATER MANAGEMENT INSERTS FROM CONSTRUCTION SITE RUNOFF.



**NOTES FOR CONSTRUCTION EQUIPMENT**

- STORMTECH SC-740 CHAMBERS SHALL BE INSTALLED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740/DC-780 CONSTRUCTION GUIDE".
- THE USE OF CONSTRUCTION EQUIPMENT OVER SC-740 CHAMBERS IS LIMITED:
  - NO EQUIPMENT IS ALLOWED ON BARE CHAMBERS.
  - NO RUBBER Tired LOADERS, DUMP TRUCKS, OR EXCAVATORS ARE ALLOWED UNTIL PROPER FILL DEPTHS ARE REACHED IN ACCORDANCE WITH THE "STORMTECH SC-310SC-740/DC-780 CONSTRUCTION GUIDE".
  - WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT CAN BE FOUND IN THE "STORMTECH SC-310SC-740/DC-780 CONSTRUCTION GUIDE".
- FULL 30" (900 mm) OF STABILIZED COVER MATERIALS OVER THE CHAMBERS IS REQUIRED FOR DUMP TRUCK TRAVEL OR DUMPING.

USE OF A DOZER TO PUSH EMBEDMENT STONE BETWEEN THE ROWS OF CHAMBERS MAY CAUSE DAMAGE TO THE CHAMBERS AND IS NOT AN ACCEPTABLE BACKFILL METHOD. ANY CHAMBERS DAMAGED BY THE "DUMP AND PUSH" METHOD ARE NOT COVERED UNDER THE STORMTECH STANDARD WARRANTY.

CONTACT STORMTECH AT 1-888-892-2694 WITH ANY QUESTIONS ON INSTALLATION REQUIREMENTS OR WEIGHT LIMITS FOR CONSTRUCTION EQUIPMENT.

**SC-740 TECHNICAL SPECIFICATION**



**NOMINAL CHAMBER SPECIFICATIONS**

|                                 |  |
|---------------------------------|--|
| SIZE (W X H X INSTALLED LENGTH) | 51.0" X 30.0" X 85.4" (1295 mm X 762 mm X 2169 mm) |
| CHAMBER STORAGE                 | 45.9 CUBIC FEET (1.30 m <sup>3</sup> )             |
| MINIMUM INSTALLED STORAGE*      | 74.9 CUBIC FEET (2.12 m <sup>3</sup> )             |
| WEIGHT                          | 75.0 lbs. (33.6 kg)                                |

\*ASSUMES 6" (152 mm) STONE ABOVE, BELOW, AND BETWEEN CHAMBERS


STUBS AT BOTTOM OF END CAP FOR PART NUMBERS ENDING WITH "B"  
 STUBS AT TOP OF END CAP FOR PART NUMBERS ENDING WITH "T"

| PART #                      | STUB         | A              | B              | C            |
|-----------------------------|--------------|----------------|----------------|--------------|
| SC740EP0E0T / SC740EP0E0TPC | 6" (150 mm)  | 10.9" (277 mm) | 18.5" (470 mm) | —            |
| SC740EP0E0B / SC740EP0E0BPC | —            | —              | 16.5" (419 mm) | 0.5" (13 mm) |
| SC740EP0E0B / SC740EP0E0BPC | 6" (200 mm)  | 12.2" (310 mm) | —              | 0.6" (15 mm) |
| SC740EP10T / SC740EP10TPC   | 10" (250 mm) | 13.4" (340 mm) | 14.5" (368 mm) | —            |
| SC740EP10B / SC740EP10BPC   | —            | —              | —              | 0.7" (18 mm) |
| SC740EP12T / SC740EP12TPC   | 12" (300 mm) | 14.7" (373 mm) | 12.5" (318 mm) | —            |
| SC740EP12B / SC740EP12BPC   | —            | —              | —              | 1.2" (30 mm) |
| SC740EP15T / SC740EP15TPC   | 15" (375 mm) | 18.4" (467 mm) | 9.0" (229 mm)  | —            |
| SC740EP15B / SC740EP15BPC   | —            | —              | —              | 1.3" (33 mm) |
| SC740EP18T / SC740EP18TPC   | 18" (450 mm) | 19.7" (500 mm) | 5.0" (127 mm)  | —            |
| SC740EP18B / SC740EP18BPC   | —            | —              | —              | 0.8" (21 mm) |
| SC740EP24T / SC740EP24TPC   | 24" (600 mm) | 18.5" (470 mm) | —              | 0.1" (3 mm)  |

ALL STUBS, EXCEPT FOR THE SC740EP24B ARE PLACED AT BOTTOM OF END CAP SUCH THAT THE OUTSIDE DIAMETER OF THE STUB IS FLUSH WITH THE BOTTOM OF THE END CAP. FOR ADDITIONAL INFORMATION CONTACT STORMTECH AT 1-888-892-2694.

\* FOR THE SC740EP24B THE 24" (600 mm) STUB LIES BELOW THE BOTTOM OF THE END CAP APPROXIMATELY 1.75" (44 mm). BACKFILL MATERIAL SHOULD BE REMOVED FROM BELOW THE N-12 STUB SO THAT THE FITTING SITS LEVEL.

NOTE: ALL DIMENSIONS ARE NOMINAL



**SC-740 6" (150 mm) INSPECTION PORT DETAIL**

- NOTE:**
- THE AREA OF INFILTRATION SYSTEMS SHALL BE EXCAVATED TO REMOVE TILL DOWN TO NATURAL SOILS AND SHALL BE AGENT OF THE TOWN PRIOR TO INSTALLING CRUSHED STONE AND THE UNDERGROUND INFILTRATION SYSTEM.
  - ESTIMATED SEASONAL HIGH GROUNDWATER ASSUMED USING TP-41. REFER TO DETAIL CALCULATION PROVIDED ABOVE.
  - LAYOUT, DESIGN, AND ELEVATIONS PRODUCED BY ADS STORMTECH DESIGN TOOL.
  - REFER TO GRADING AND DRAINAGE NOTE 20 ON SHEET 2.

**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:  
 FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY DEVELOPMENT**  
 SUMMER STREET  
 WALPOLE, MA

**REVISIONS:**

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



**SITE PLAN**

**STORMTECH INFILTRATION SYSTEM #4 (DETAIL SHEET 23 OF 27)**

|                 |               |
|-----------------|---------------|
| DATE:           | JUNE 20, 2023 |
| PROJECT NUMBER: | 19097         |
| DESIGNED BY:    | PB/KE/KF      |
| DRAWN BY:       | PB/MB/KF/KL   |
| CHECKED BY:     | KE            |
| C.61            |               |

SHEET 61 OF 65

**CEDAR RIDGE WETLAND REPLICATION PLAN**

1. THE REPLICATION AREA PLANTING HAS BEEN PRODUCED BY BRIAN BUTLER OF OXBOW ASSOCIATES.
2. THE CONSTRUCTION OF COMPENSATORY WETLAND FOR ALTERATION OF BORDERING VEGETATED WETLAND (BWV) IS PROPOSED IN 2 LOCATIONS. THE LOCATIONS CHOSEN AND THE METHODOLOGY EMPLOYED FOR THE REPLICATION EFFORT ARE COMPLIANT WITH THE APPLICABLE STANDARDS AT 310 CMR 10.055 (4) (B);
- 2.1. THE SURFACE OF THE REPLACEMENT AREA TO BE CREATED ("THE REPLACEMENT AREA") SHALL BE EQUAL TO THAT OF THE AREA THAT WILL BE LOST ("THE LOST AREA");
3. THE AGGREGATE ALTERED AREA EQUALS LESS THAN 4,567 SQUARE FEET WITH THE REDUCTION OF THE CROSSING 1 FOOTPRINT. THE PROPOSED 7,106 SQ. FT. REPLICATION EXCEEDS AN IMPACT TO REPLICATION RATION OF 1:1.55.
- 3.1. THE GROUND WATER AND SURFACE ELEVATION OF THE REPLACEMENT AREA SHALL BE APPROXIMATELY EQUAL TO THAT OF THE LOST AREA;
4. THE LOCATIONS (2) WERE CHOSEN BOTH FOR ADJACENCY AND CONSISTENCY WITH THE SAME SUBDRAINAGE, AS WELL AS TO APPROXIMATE THE IMPACTED ELEVATIONS AND AMBIENT GROUNDWATER CONDITIONS. THE ALTERATION AT CROSSING 1 IS AT +/- 208 ELEVATION, AS ARE THE PROPOSED REPLACEMENT AREAS. SIMILARLY, CROSSING 2 IS AT +/- 208 ELEVATION AND FINAL GRADES ARE ANTICIPATED TO BE BETWEEN 206 AND 208.
- 4.1. THE OVERALL HORIZONTAL CONFIGURATION AND LOCATION OF THE REPLACEMENT AREA WITH RESPECT TO THE BANK SHALL BE SIMILAR TO THAT OF THE LOST AREA;
5. THE LOCATIONS WERE ADAPTED SO AS TO BE ADJACENT AND PARALLEL TO THE IMPACTED SYSTEMS (SEE SHEET C.87, REV. 9/14/20).
- 5.1. THE REPLACEMENT AREA SHALL HAVE AN UNRESTRICTED HYDRAULIC CONNECTION TO THE SAME WATER BODY OR WATERWAY ASSOCIATED WITH THE LOST AREA;
6. THE LOCALITIES CHOSEN FOR THE COMPENSATORY REPLICATION WERE IDENTIFIED BASED UPON THEIR ADHERENCE TO THIS CRITERIA. THEY ARE WITHIN FEET OF THE IMPACT AND ANNECTANT OR CONFLUENT WITH THE PARENT RESOURCE AREA(S).
- 6.1. THE REPLACEMENT AREA SHALL BE LOCATED WITHIN THE SAME GENERAL AREA OF THE WATER BODY OR REACH OF THE WATERWAY AS THE LOST AREA;
7. THE LOCATION OF THE 2 REPLICATION POLYGONS IS IMMEDIATELY ADJACENT TO THE IMPACTED AREAS AND THEREFORE MEETS THIS STANDARD.
- 7.1. AT LEAST 75% OF THE SURFACE OF THE REPLACEMENT AREA SHALL BE REESTABLISHED WITH INDIGENOUS WETLAND PLANT SPECIES WITHIN TWO GROWING SEASONS, AND PRIOR TO SAID VEGETATIVE REESTABLISHMENT ANY EXPOSED SOIL IN THE REPLACEMENT AREA SHALL BE TEMPORARILY STABILIZED TO PREVENT EROSION IN ACCORDANCE WITH STANDARD U.S. SOIL CONSERVATION SERVICE METHODS;
8. THE PROPOSED REPLICATION PLANS, QUANTIFIED IN THE ACCOMPANYING TABLES WILL MEET THE 75% THRESHOLD, OR, IF NECESSARY WILL BE SUPPLANTED DURING THE TWO-SEASON MONITORING PERIOD. THE SPECIES COMPOSITION AND PREFERRED GROUND TREATMENT (USE OF NATIVE LITTER IF POSSIBLE) ARE IN KEEPING WITH SPECIES NATIVE TO THE AREA AND THE SITE.
- 8.1. THE REPLACEMENT AREA SHALL BE PROVIDED IN A MANNER WHICH IS CONSISTENT WITH ALL OTHER GENERAL PERFORMANCE STANDARDS FOR EACH RESOURCE AREA IN PART III OF 310 CMR 10.00. THE REPLACEMENT AREA MEETS OR EXCEEDS THE APPLICABLE STANDARDS.

**SITE PREPARATION AND PLANTING**

TOPOGRAPHY IN EACH REPLICATION SITE (2) IS VARIABLE. THE ADJACENT FACES (TO WETLAND) ARE CONTIGUOUS WITH EXISTING BWV AND THE ADJACENT CONSTRUCTION OF THE AREAS WILL PROVIDE A 'BORDERING' CONDITION IN KEEPING WITH THE REPLICATION STANDARDS.

EACH REPLICATION SITE HAS BEEN EXAMINED FOR PRACTICALITY OF IMPLEMENTATION; SPECIFICALLY, THAT NO RADICAL CUTS, ROCK OUTCROPS OR OTHER OBSTACLES TO THE REQUIRED GRADING ARE PRESENT. EACH SITE WILL BE ISOLATED, AT THE BWV BOUNDARY WITH STAKED SILTATION FENCE AND STRAW WATTLES TO FORM A LIMIT OF WORK AND EROSION BARRIER. TREES AND VEGETATION WILL BE CUT AND STUMPS REMOVED AS NEEDED. LEAF LITTER WILL BE GATHERED AND STOCKPILED IF SEASONALLY PRACTICAL.

SOIL WILL BE REMOVED FROM EACH AREA TO A POINT AT LEAST 12 INCHES BELOW SEASONAL HIGH GROUNDWATER. EXAMINATION OF SOILS CHARACTERISTICS BY A WETLAND SCIENTIST WILL SET THE FINAL, OVER-EXCAVATED ELEVATION, ASSURING RELIABLE INTERCEPTION OF LOCAL SEASONAL GROUNDWATER. SOIL FROM THE IMPACT AREAS WILL NOT BE UTILIZED IN THE REPLACEMENT AREAS DUE TO THE PRESENCE OF INVASIVE PROPAGULES AND THE RELATIVELY LOW ORGANIC CONTENT OF THE IMPACT AREA SOILS. CLEAN, WEED-FREE LOAM WITH UP TO 40% HOT-COMPOSTED MATERIAL WILL BE SPREAD AT A DEPTH OF APPROXIMATELY 6" THROUGHOUT THE REPLICATION AREAS AND LIGHTLY COMPACTED.

DURING A SUITABLE SEASONAL PERIOD (AVOIDING MID-WINTER AND LATE SUMMER) TREE AND SHRUB PLANTINGS WILL BE INSTALLED. SPECIES WILL BE DRAWN FROM THE LIST IN TABLE 2, WITH NOT LESS THAN THREE SPECIES IN EACH CATEGORY. PLANTINGS WILL BE WATERED AND/OR STAKED AS NECESSARY. AT THE COMPLETION OF PLANTING ONE OF TWO FINISH TREATMENTS WILL BE APPLIED. IF SUFFICIENT LEAF-LITTER FROM UPLAND SITE AREAS EXHIBITING LOW INVASIVES (BUCKTHORN, BARBERRY, HONEYSUCKLE) CAN BE GATHERED AND STOCKPILED WITHOUT BEING LOST TO COMPOSTING ACTION, THIS WILL BE THE PREFERRED GROUND COVER. TREES AND SHRUBS WILL BE PLANTED PRIOR TO GROUND COVER; HERBACEOUS PLUGS WILL BE INSTALLED THROUGH THE LEAF LITTER. IF RETENTION OF SUITABLE LEAF LITTER MATERIAL IS IMPRACTICAL DUE TO SEASONAL SCHEDULING, OR IF IT CAN ONLY BE SOURCED ON SITE WHERE INVASIVE SPECIES MAY BE PROBLEMLIC, THE SOIL SURFACE WILL BE RAKED, AND SEEDED AT TWO TIMES THE RECOMMENDED RATE WITH A NATIVE NEW ENGLAND WETLAND SEED MIX (NE WETLAND PLANTS OR APPROVED EQUIVALENT). PLUG PLANTINGS WILL FOLLOW THIS TREATMENT. SEEDLESS STRAW MAY BE UTILIZED TO RETAIN SOIL MOISTURE AND DISCOURAGE SEED LOSS, PARTICULARLY IF SEEDING IS LATE IN THE SEASON.

THE REPLICATION AREAS SHALL BE CONSTRUCTED IN CONJUNCTION WITH THE ADJACENT ROAD CONSTRUCTION. THE PLANTING SHALL BE COMPLETED DURING THE FIRST GROWING SEASON AFTER START OF SITE CONSTRUCTION.

**MONITORING**

ALL GROWTH WILL BE MONITORED TWICE PER YEAR FOR TWO COMPLETE GROWING SEASONS FOLLOWING INSTALLATIONS. IN THE EVENT THAT LESS THAN 80% OF PLANTINGS SURVIVE, REPLACEMENTS WILL BE INSTALLED TO ASSURE A MINIMUM OF 75% HYDROPHYTIC COVERAGE.

PLANTING DENSITIES PROPOSED ANTICIPATE MATURITY OF TREE AND SHRUB SPECIMENS, DELIBERATELY AVOIDING OVERSHADING OF UNDERSTORY PLANTINGS UNTIL THEY HAVE HAD MULTIPLE SEASONS OF GROWTH WITH ADEQUATE INSULATION TO BECOME ESTABLISHED.

Table 1. Planting densities for the respective replication areas (see plan set).

| Planting Category | Replication Area 1 | Replication Area 2 |
|-------------------|--------------------|--------------------|
| Trees             | 35                 | 24                 |
| Shrubs            | 230                | 165                |
| Herbaceous Plugs  | 450                | 330                |
| Native Wet Mix*   | 2x recommended     | 2x recommended     |


Table 2. Species list of acceptable plantings - at least 3 of tree and shrub species to be planted.

| Category          | Species                            | Common Name        | Notes                          |
|-------------------|------------------------------------|--------------------|--------------------------------|
| Tree              | <i>Acer rubrum</i>                 | Red Maple          | Only specimens >8'             |
| Tree              | <i>Fraxinus pennsylvanicum</i>     | Green Ash          |                                |
| Tree              | <i>Quercus bicolor</i>             | Swamp White Oak    |                                |
| Tree              | <i>Quercus palustris</i>           | Pin Oak            |                                |
| Tree              | <i>Ulmus americana*</i>            | American Elm*      | *Resistant hybrid only         |
| Shrub             | <i>Lindera benzoin</i>             | Spicebush          |                                |
| Shrub             | <i>Ilex verticillata</i>           | Winterberry Holly  | Plant in groups of 2-4         |
| Shrub             | <i>Viburnum recognitum</i>         | Northern Arrowwood | Plant in groups of 2-4         |
| Shrub             | <i>Vaccinium corymbosum</i>        | Highbush blueberry | Plant in groups of 2-4         |
| Shrub             | <i>Viburnum trilobum</i>           | Highbush cranberry | Plant in groups of 2-4         |
| Herb. Plugs       | <i>Onoclea sensibilis</i>          | Sensitive fern     |                                |
| Herb. Plugs       | <i>Osmundastrum cinnamomeum</i>    | Cinnamon fern      |                                |
| Herb. Plugs       | <i>Osmunda regalis</i>             | Royal fern         |                                |
| Herb. Plugs       | <i>Carex stricta</i>               | Tussock sedge      |                                |
| Seed Mix          | <i>New England Native Wet Mix</i>  | NE Wetland Plants  | Or approved mix                |
| Alt. Ground Cover | <i>Salvaged native leaf mulch*</i> |                    | *Subs for seed mix if possible |



\*NOTE: PLANTINGS MAY BE BUMPED UP BY 10% TO INCREASE DENSITY IF DESIRED

**TOWN OF WALPOLE CONSERVATION COMMISSION NOTES:**

1. INCLUDE LOCATION OF THE NO ALTERATION SIGNS APPROXIMATELY EVERY 150- FEET ON SITE PLAN (TAKING INTO CONSIDERATION THE TWISTS AND TURNS OF THE WETLAND BOUNDARIES TO DETERMINE LOCATIONS) WITH SIGN SPECIFICALLY AT REPLICATION AREAS AND CROSSING. SHOW ON SITE PLAN PET WASTE REMOVAL SIGNS AT BOTH ENDS OF RIVERFRONT WHERE TRAIL BEGINS AND ENDS. PET WASTE PICK UP IS REQUIRED UNDER THE BYLAW.
2. INCLUDE LANDSCAPE PLAN FOR AREAS WITHIN THE 100-FOOT BUFFER ZONE SPECIFYING INVASIVE SPECIES MAINTENANCE PLAN, REMOVAL OF GRASS CLIPPING AND CUTTINGS OUTSIDE THE BUFFER ZONES, LIMIT USE OF NON-ORGANIC FERTILIZERS AND NO HERBICIDES OR PESTICIDES, AND DROUGHT RESISTANT NATIVE PLANTINGS.



**NOTE:**  
1. WETLAND REPLICATION AREA - 1.5:1. TOTAL REPLICATION AREA = 7,106 S.F.



**HOWARD STEIN HUDSON**  
114 Turnpike Road, Suite 2C  
Chelmsford, MA 01824  
www.hshassoc.com

PREPARED FOR:  
FRH REALTY LLC  
c/o FAIRFIELD RESIDENTIAL  
5 BURLINGTON WOODS, SUITE 203  
BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY DEVELOPMENT**  
SUMMER STREET  
WALPOLE, MA

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |



**SITE PLAN**

**WETLAND REPLICATION AREAS (DETAIL SHEET 26 OF 27)**

DATE: JUNE 20, 2023  
PROJECT NUMBER: 19097  
DESIGNED BY: PB/KE/KF  
DRAWN BY: PB/MB/KF/KL  
CHECKED BY: KE  
C.64  
SHEET 64 OF 65





**HOWARD STEIN HUDSON**  
 114 Turnpike Road, Suite 2C  
 Chelmsford, MA 01824  
 www.hshassoc.com

PREPARED FOR:

FRH REALTY LLC  
 c/o FAIRFIELD RESIDENTIAL  
 5 BURLINGTON WOODS, SUITE 203  
 BURLINGTON, MA 01803

**PROPOSED MULTIFAMILY  
 DEVELOPMENT  
 SUMMER STREET  
 WALPOLE, MA**

REVISIONS:

| NO | BY | DATE     | DESCRIPTION            |
|----|----|----------|------------------------|
| 1  | PB | 08/31/23 | REV. PER PEER REVIEW   |
| 2  | PB | 09/12/23 | REV. TRAIL AND SEEDING |
| 3  | MB | 09/20/23 | REV. TOWN/PEER COMM.   |








SITE  
 PLAN

REPLICATION AREA  
 PROFILES  
 (DETAIL SHEET  
 27 OF 27)

DATE: JUNE 20, 2023  
 PROJECT NUMBER: 19097  
 DESIGNED BY: PB/KE/KF  
 DRAWN BY: PB/MB/KF/KL  
 CHECKED BY: KE

C.65

SHEET 65 OF 65



9/21/2023 L:\19097\19097 04 - Lot 2\CURRENT\19097 - Details.dwg  
 last saved by: MB/KF/KE  
 printed by: Matthew Baker